

Trevoole, Praze, Camborne, Cornwall, England, TR14 0PJ Tel: +44 (0) 1209 831 500 | Fax: +44 (0) 1209 831 939 sales@grosvenorpumps.com | www.grosvenorpumps.com

Invikta - Constant Dosage



A simple yet reliable series of compact, microprocessor controlled solenoid dosing/metering pumps.

Typical applications include Swimming Pools, Car Wash, Cooling Towers & RO systems.

Robust IP65 Polypropylene enclosure protects against jest of water and aggressive environments. Can be mounted directly onto surface or via the supplied fixing bracket, allowing quick removal.

Pumphead has manual priming valve, with flow rate adjustment, from 0 to 100%, via front panel potentiometer.

LED provides indication of pump operationg status. Can be equipped with low level alarm upon request.

All Invikta units are supplied with an Installation Kit comprising of a Fixing Bracket, Suction Tubing, Delivery Tubing, Foot Filter and Injection Connector.

Wetted Materials

Pumphead: PVC

Ball Valves: Pyrex Glass

Seals & Valves: FPM or EPDM

Diaphragm: PTFE

Suction Tube: PVC

Delivery Tube: PE

Tube Connections: 4/6 mm

Supply Voltage: 90-265/1/50-60 (20-60/1/50-60 Upon Reguest)



